(19) World Intellectual Property **Organization**

International Bureau





(43) International Publication Date 22 September 2005 (22.09.2005)

PCT

(10) International Publication Number WO 2005/088973 A1

(51) International Patent Classification⁷:

H04N 7/26

(21) International Application Number:

PCT/IB2005/050637

(22) International Filing Date: 22 February 2005 (22.02.2005)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

04100806.1

1 March 2004 (01.03.2004)


- (71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): VAREKAMP, Christiaan [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). WILINSKI, Piotr [PL/NL];

c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL). SCHRODERS, Mark, F., A. [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

- (74) Agents: GROENENDAAL, Antonius, W., M. et al.; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

[Continued on next page]

(54) Title: A VIDEO SIGNAL ENCODER, A VIDEO SIGNAL PROCESSOR, A VIDEO SIGNAL DISTRIBUTION SYSTEM AND METHODS OF OPERATION THEREFOR



(57) Abstract: A video encoder (100) comprises a receiver (101) which receives an uncompressed video signal. An encoding element (103) generates a compressed video signal in accordance with a compression algorithm, such as an MPEG-2 encoding algorithm. In addition, a feature point processor (105) generates feature point data (105) in response to the uncompressed signal, and an output processor (107) generates an output video signal which comprises the compressed video signal and the feature point data. The output signal is received by a receiver (201) of a video signal processor (200). An extraction processor (203) extracts the feature point data and feeds it to a video processor unit (207) which processes the compressed video signal in response to the feature point data. The separate and independent generation of feature point data, such as feature point movement data or tracks using the uncompressed (original) video signal, eliminates or reduces the impact of compression artifacts, inaccuracies and errors on feature point locations and trajectories when these are detected using the compressed signal.



WO 2005/088973 A1



SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

with international search report